



# ORDER GUIDE

## UC130-SVS

SYSTEM	APPLICATION	WHEEL TURNS	COMPONENTS	MODEL	QTY
<b>Single Engine Single Cylinder</b>  	Up to 350 hp max	5.5 (UP25)	Cylinder	UC130-SVS	1
			Helm pump	UP25 or UP33-SVS	1
			Hose Kit	KIT OB-SVS	1
		3.9 (UP33)	Oil	OIL 15	2
			Steering wheel	(Wheel selection)	1


For a second station add:

1 UP25-SVS or UP33-SVS helm pump, 1 KIT OB-2S fitting kit, 1 KIT OB-SVS, 1 OIL 15, 1 steering wheel

<b>Dual engine Single cylinder</b>  	Up to 350 hp max (non-counter rotating engine)  Up to 600 hp max (counter rotating engine)	5.5 (UP25)	Cylinder	UC130-SVS	1
			Helm pump	UP25 or UP33-SVS	1
			Hose Kit	KIT OB-SVS	1
		3.9 (UP33)	Oil	OIL 15	2
			Tie bar	A94	1
	Steering wheel	(Wheel selection)	1		

For a second station add:

1 UP25-SVS or UP33-SVS helm pump, 1 KIT OB-2S fitting kit, 1 KIT OB-SVS, 1 OIL 15, 1 steering wheel

<b>Dual engine Dual cylinder</b>  	Up to 600 hp max (non-counter rotating engines)	6.6 (UP39)	Cylinder	UC130-SVS	1	
			Cylinder Port	UC130P-SVS	1	
			Helm pump	UP39-SVS	1	
			Hose Kit	KIT OB-SVS	1	
	Up to 700 hp max (counter rotating engines)			Oil	OIL 15	3
				Tie bar	A90	1
				Steering wheel	(Wheel selection)	1
				Connection Kit	KIT OB-DBR-SVS	1

For a second station add:

1 UP39-SVS helm pump, 1 KIT OB-2S fitting kit, 1 KIT OB-SVS, 2 T fittings 39502 V, 1 OIL 15, 1 steering wheel

### WARNING

The UC130-SVS front mount cylinder is not recommended for use in installations where the boat speed exceeds 69 mph (60 knots); (75 mph (65 knots) in dual engine, dual cylinder and counter rotating engines application). Not intended for use in racing application.

### ATTENTION:

The SilverSteer helm pumps are always to be installed in conjunction with the UC130-SVS cylinder and the Kevlar reinforced hose kit KIT OB-SVS